

Features & Benefits

- 🔥 Protects against rust and corrosion
- 🔥 Reduces friction – provides constant torque/tension
- 🔥 Speeds assembly / disassembly
- 🔥 Prevents seizing, galling and cold welding
- 🔥 Retards galvanic action between dissimilar metals
- 🔥 Resists salt water corrosion
- 🔥 Compatible with all types of metals and most plastics
- 🔥 Non-hardening and non-dripping

Description

Permabond Anti-Seize is a superior grade assembly compound and high pressure lubricant. This high quality aluminum, copper and graphite based antiseize formula has unique particle shapes suspended in special carriers. It will protect metal parts under extreme heat, pressure and contaminating conditions to 2000°F (1095°C).

AntiSeize is designed with ultra-fine metallic and graphite particles enhancing a longer lasting protective film, resisting washout, burn-off and corrosion.

Physical Properties

Colour	Silver Grey
Appearance	Homogenous Paste
Corrosivity	Non-corrosive to ferrous metals
Operating temperature	300°F (184°C) to 2000°F (1095°C)
Specific Gravity	1.2
Weight per gallon	10.0 lb
Penetration, D217-60T, 100-3000 strokes	320-350
Oil separation, 30hr at 158°F	<1%
Flash point	>350°F (177°C)
Friction coefficient	0.10
Torque coefficient	K Values 0.15±0.02 (testing recommended on individual fastener type)
Solid lubricants (aluminum, copper, graphite)	42%

Storage & Handling

Storage Temperature	41 to 80°F (5 to 25°C)
Shelf Life Stored in original unopened containers	12 months

Additional Information

Users are reminded that all materials, whether innocuous or not, should be handled in accordance with the principles of good industrial hygiene. Full information can be obtained from the Material Safety Data Sheet.

Contact Permabond:

Europe: Tel. +44 (0)1962 711661
UK Helpline: 0800 975 9800
Deutschland: 0800 10 13 177
France: 0805 11 13 88
info.europe@permabond.com

US: Tel. +1 732-868-1372
Helpline: 800-640-7599
info.americas@permabond.com
Asia: Tel. +86 21 5773 4913
info.asia@permabond.com

www.permabond.com

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers before using any product in full-scale production make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. THE PRODUCTS DISCLOSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED.

No representative of ours has any authority to waive or change the foregoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of this patent. We also expect purchasers to use our products in accordance with the guiding principles of the Chemical Manufacturers Association's Responsible Care® program.